

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : 1-METHOXY-2-PROPANOL

1. Product and Company Identification

Product name: 1-Methoxy-2-propanol
Synonyms: alpha-Propylene glycol monomethyl ether; alpha-PGME
Item Numbers: E48010100

European Contact Details

Edwards, Manor Royal, Crawley
West Sussex, RH10 9LW, England
E-mail: info@edwardsvacuum.com

General enquiries

UK : +44 (0)1293 528844
France : +(33) 1 47 98 24 01
Germany : +(49) 6420-82-410
Italy : +(39) 0248-4471

US Contact Details

Edwards, Three Highwood Drive, Suite 3-10E,
Highwood Office Park, Tewksbury, MA 01876

General enquiries

+(1) 978-658-5410
Toll Free: 1-800-848-9800

24 h Emergency telephone number:

Chemtrec: 1-800-424-9300

2. Hazards Identification

Highly flammable liquid and vapour. Avoid heat, sparks, and flame. Flash back may occur from vapours to a source of ignition.

Prolonged or repeated contact causes defatting of the skin with irritation, dryness and cracking. May cause central nervous system depression. May cause eye, skin, and respiratory tract irritation.

For short and long term exposure effects see Section 11 Toxicological data.

Eye Effects: May cause eye irritation.

Skin Effects: May cause skin irritation. May be harmful if absorbed through the skin. Prolonged and/or frequent contact may cause drying, cracking or folliculitis.

Ingestion/Oral Effects: May cause gastrointestinal irritation with nausea, vomiting and diarrhoea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

Inhalation Effects: Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, Inhalation: dizziness, unconsciousness and coma. Causes respiratory tract irritation. May be harmful if inhaled. Vapours may cause dizziness or suffocation.

Chronic: Repeated or prolonged exposure may cause stimulation of the central nervous system.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : 1-METHOXY-2-PROPANOL

NFPA Hazard codes		HMIS Hazard codes		Rating System
Health	1	Health	1	0 = No Hazard
Flammability	3	Flammability	3	1 = Slight Hazard
Instability	0	Reactivity	0	2 = Moderate Hazard
				3 = Serious Hazard
				4 = Severe Hazard

3. Composition/Information on Ingredients

Ingredient	% Weight	CAS No	Hazard class*	Risk phrase*
1-Methoxy-2-propanol	98.5	107-98-2	3	R10
2-Methoxypropanol	< 0.5	1589-47-5	Not applicable	Not applicable

*Hazard class & Risk phrase. These columns are only completed for ingredients which are classified as hazardous under EU Directive No 1272/2008 (as amended) and are present in sufficient concentration to make the overall substance hazardous. In all other situations, the column will be completed as "Not applicable".

4. First Aid Measures

Eyes:	Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.
Skin:	Get medical aid. Wash skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before use.
Ingestion/Oral:	Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately.
Inhalation:	Remove the victim to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.
Other Information:	None.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : 1-METHOXY-2-PROPANOL

5. Fire Fighting Measures

- Extinguishing Media:** For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.
For large fires, use water spray, fog, or alcohol-resistant foam.
Water may be ineffective. Do NOT use straight streams of water.
Cool containers with flooding quantities of water until well after fire is out.
- Fire and Explosion Hazard:** Liquid and vapours are flammable. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. Vapours may be heavier than air, spread along the ground and collect in low or confined areas. Containers may explode in the heat of a fire.
- Special Protective Equipment for Fire Fighters:** Use MSHA/NIOSH (approved or equivalent) self-contained breathing apparatus in pressure-demand mode, and full protective gear. During a fire, irritating, corrosive and toxic gases may be generated by thermal decomposition or combustion of the product. Wear the appropriate protective clothing to prevent contact with skin and eyes.

For Flammability Properties - see Section 9.

6. Accidental Release Measures

Do not walk through or otherwise scatter or spread any spilled product. Put on the appropriate protective equipment (See Section 8) and clean up spills immediately. (Use spark-proof tools.) Isolate the area of the spill and dike well ahead of large spills for later recycling or disposal.

Ventilate enclosed areas. Use a suppressing foam to reduce vapours. (Water spray may reduce vapour but may not prevent ignition in closed spaces).

Use inert material (for example, vermiculite, dry sand or earth) to absorb the spilled product, and then place it into a chemical waste container. Do not use combustible materials such as sawdust to absorb the product. Safely dispose of the recovered spilled product (See Section 13).

Avoid run-off into storm sewers, drains and ditches that lead to waterways.

7. Handling and Storage

Handling: Wear appropriate protective equipment. Use only in a well-ventilated area. Do not inhale fumes or vapours from the product. Earth (ground) and bond containers when transferring product. Use spark-proof tools and explosion proof equipment. Keep away from incompatible materials (See Section 10).

Empty containers retain product residue (liquid and/or vapour) and can be dangerous. Take precautionary measures against static discharges. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.

Do not get the product in eyes, on skin, or on clothing. Do not ingest the product. Do not eat, drink, or smoke in areas where this product is used. Wash thoroughly after handling. Immediately remove contaminated clothing and wash before reuse.

Storage: Store in tightly closed containers, in a dedicated flammables area. Store in a cool, dry, well-ventilated area away from incompatible materials (See Section 10). Keep away from heat, sparks, flames, and sources of ignition. Do not store in direct sunlight.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : 1-METHOXY-2-PROPANOL

8. Exposure Controls/Personal Protection

Exposure Limits:

Ingredient	ACGIH - TLV -	OSHA - PEL	Occupational Exposure Limits EH40 (UK)
1-Methoxy-2-propanol	100 ppm 150 ppm - STEL	None Established	100 ppm TWA 360 mg/m ³ TWA

Personal Protection:

Engineering Measures:	Use explosion proof ventilation equipment. Provide eyewash facilities and safety showers. Ensure adequate ventilation in areas where the product is used, to keep airborne concentrations low.
Respiratory Protection:	Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator, in the positive pressure mode with emergency escape provisions, whenever workplace conditions warrant a the use of a respirator.
Hand/Skin Protection:	Wear appropriate protective and chemical-resistant gloves, clothing and splash protection, or fully encapsulating vapour protective clothing, as necessary to prevent exposure.
Eye/Face Protection:	Wear appropriate chemical safety goggles with full face shield.
Hygiene Measures:	Do not eat, drink or smoke while using the product. Wash hands after using the product and before eating, drinking or smoking. Immediately change contaminated clothing.
Other/General Protection:	Overalls should be laundered regularly.

9. Physical and Chemical Properties

Appearance and Odour	Colourless liquid, sweetish/ ethereal odour	Boiling point	118-119 / 244-246	°C/°F
pH (as supplied)	4 to 7 (200 g/l @ 20 °C)	Freezing Point	-97 / -143	°C/°F
Solubility in Water	Soluble	Auto Ignition	286 / 547	°C/°F
Volatile Content by Volume	≥ 98.5%	Flash Point	33 / 91	°C/°F
Specific Gravity	0.92			
Vapour Pressure (mbar)	14.5 @ 25 °C	Vapour Pressure (Torr)	10.9 @ 77 °F	

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : 1-METHOXY-2-PROPANOL

10. Stability and Reactivity

Stability:	Stable under normal handling and storage conditions.
Material/Conditions to Avoid:	Avoid ignition sources and excess heat. Keep away from strong oxidizing agents, sulphuric acid, isocyanates, acid anhydrides, perchloric acid and acid chlorides.
Hazardous Decomposition:	Carbon monoxide and carbon dioxide are evolved during combustion.
Hazardous Polymerisation:	Has not been reported.

11. Toxicological Information

For a comprehensive description for the various toxicological (health) effects which may arise if the user comes into contact with the substance or preparation refer to Section 2 Hazards Identification.

Animal data:

LD50 value: Oral, mouse: 11700 mg/kg. Oral, rabbit: 5700 mg/kg. Oral, rat: 6600 mg/kg.
Dermal, rabbit: 13 g/kg.

LC50 value: Inhalation, rat: LC50 = 10000 ppm/5hr.

Carcinogenicity:

No known carcinogenic effects.

12. Ecological Information

Persistence:	No data available.
Biodegradability:	No data available.
Mobility:	No data available.
Bioaccumulation:	No data available.
Ecotoxicity:	LC50 (aquatic): 19202 mg/l (96 hr).
Other Information:	Aquatic ecotoxicity: Fathead Minnow: LC50 = 15886 mg/l (96 hr). Bluegill/Sunfish: LC50 = 21742 mg/l (96 hr). Water flea: EC50 = 10457 mg/l (96 hr).

13. Disposal Considerations

If recycling is not practicable, dispose of the product and used containers in accordance with all local and national requirements.

Empty containers must be decontaminated before recycling.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : 1-METHOXY-2-PROPANOL

14. Transport Information

This product is classified as dangerous under transport regulations.

PARAMETER	EUROPEAN	CANADIAN TDG	UNITED STATES DOT
Proper Shipping Name	1-METHOXY-2-PROPANOL	1-METHOXY-2-PROPANOL	1-METHOXY-2-PROPANOL
Hazard Class	3	3	3
Identification Number	UN 3092	UN 3092	UN 3092
Shipping Label	FLAMMABLE LIQUID	FLAMMABLE LIQUID	FLAMMABLE LIQUID

Packing Group: III

15. Regulatory Information

European Regulatory Information

CAS no: 107-98-2 has been classified in accordance with EU Regulation No 1272/2008 (as amended) on the Classification, Labelling and Packaging of Substances and Mixtures.

Classified as dangerous to supply: Yes.

Risk Phrases: R 10 Flammable.

Safety Phrases : S 24/25 Avoid contact with skin and eyes.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Symbols: F

WGK (Water Danger/Protection) 1 (for CAS no: 107-98-2).

United States Regulatory Information

CAS no: 107-98-2 is listed on the U.S. Toxic Substances Control Act (TSCA).

SARA TITLE III - SECTION 313 SUPPLIER NOTIFICATION:

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act (EPCRA) of 1986 and 40 CFR Part 372.

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer or reproductive toxicity.

OSHA Regulatory Status: This material is classified as dangerous under OSHA regulations.

Canadian Regulatory Information

CAS no: 107-98-2 is included on the Canadian DSL.

WHMIS Classification: B2.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : 1-METHOXY-2-PROPANOL

16. Other Information

This MSDS is compiled in accordance with ANSI Z400.1 and Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Sources of information for this data sheet:

- Acros Organics "1-Methoxy-2-propanol" Material Safety Data Sheet no: 92566. Revision no: 7. Date 20/07/2009.

Glossary:

ACGIH - American Conference of Governmental Industrial Hygienists; **ANSI** - American National Standards Institute; **BCF** - Bioconcentration Factor; **Canadian TDG** - Canadian Transportation of Dangerous Goods; **CAS** - Chemical Abstracts Service; **Chemtrec** - Chemical Transportation Emergency Center (US); **DSL** - Domestic Substances List; **EC** - Effective concentration; **EH40 (UK)** - HSE Guidance Note EH40 Occupational exposure limits; **EPCRA** - Emergency Planning and Community Right-to-Know Act; **HMIS** - Hazardous Material Information Service; **LC** - Lethal Concentration; **LD** - Lethal Dose; **MSHA** - Mine Safety and Health Administration; **NFPA** - National Fire Protection Association; **NIOSH** - National Institute for Occupational Safety and Health; **OSHA** - Occupational Safety and Health Administration, US department of Labour; **PEL** - Permissible exposure limit; **SARA (Title III)** - Superfund Amendments and Reauthorization Act; **SARA 313** - Superfund Amendments and Reauthorization Act, Section 313; **STEL** - Short Time Exposure Limit; **TLV** - threshold limit value; **TSCA** - Toxic Substances Control Act Public Law 94-469; **US DOT** - US Department of Transportation; **WHMIS** - Workplace Hazardous Materials Information System.

Revisions:

October 2010 - Data Sheet updated to reflect the latest supplier safety information.

Although the information and recommendations in this data sheet are to the best of our knowledge correct, it is recommended that you make your own determination of the material's suitability for your purpose before you use it. The information contained in this data sheet has been reproduced from the manufacturers data; the accuracy of this information is the responsibility of the manufacturer. Edwards accept no responsibility for damage of any nature resulting from the use of, or the reliance upon, this data sheet.